



VACUUM PACKING MACHINES



Vacuum packing machine SV-310T TABLE TOP UNIT. 10 M³/H. 314 MM. • 314 mm. sealing bar • Vacuum controlled by time.		TECHNICAL SPECIFICATIONS Pump capacity: 10 m3/h Useful length of the sealing bar: 314 mm Loading: 370 W Vacuum pressure (maximum): 2 mbar Internal dimensions -internal dimensions - width: 330 mm -internal dimensions - depth: 360 mm -internal dimensions - height: 140 mm			
			 Improves the durability of cooked or raw for timer controlling the vacuum process and the preset time. Stainless steel body. Stainle Cordless sealing bar. Softair as standard. cycle stage whilst performing. STOP key a stage, moving on to the next step. Pump of of the machine. Working hours counter dis must be replaced. NSF-International certif Cleaning and Food Material regulations). 	e sealing of the pack to match the ss steel deep-drawn chamber. • Digital keyboard. • LED's indicate each allows the interruption of the cycle at any lrying program: improves the durability play, which allows to know when oil	External dimensions •Width: 384 mm •Depth: 455 mm •Height: 405 mm Net weight: 34 Kg
			nsert plate set. · · · · · · · · · · · · · · · · · · ·	OPTIONAL EQUIPMENT Vac-Norm external vacuum kit. Bag cutting kit. Liquid insert plate set. Vacuum sealing bags.	
AENOR Empresa Registrada ER-0437/196 UNE-EN ISO 9001 SAMMIC, S.L. Basarte, 1 : 20720 AZKOITIA	E NSF.				